



NOTES:

1. THE ALPHABETS AND LATERAL SPACING BETWEEN LETTERS AND NUMERALS SHALL CONFORM WITH THE TEXAS "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS", LATEST EDITION, AND ANY APPROVED CHANGES THERETO. LATERAL SPACING OF TEXT SHALL PROVIDE A BALANCED APPEARANCE. ALL MATERIALS SHALL CONFORM TO TXDOT DEPARTMENT SPECIFICATIONS FOR SMALL STREET SIGNS.
2. SIGN BLANKS SHALL BE 0.080" THICK AND ONE PIECE SHEET ALUMINUM ALLOY EXTRUDED BLADE CONFORMING WITH TXDOT DEPARTMENT SPECIFICATION "ALUMINUM SIGNS (TYPE A)."
3. SIGN BACKGROUND SHALL BE AVERY T-6500 (WHITE) HIGH INTENSITY PRISMATIC (HIP) REFLECTIVE SHEETING MATERIAL MEETING ASTM D4956 (AASHTO M268) TYPE III SPECIFICATIONS.

FOREGROUND CONSISTS OF AN OVERLAY OF GREEN AVERY SERIES OL-2007 ELECTRO-CUT FILM MEETING ASTM D4956 SPECIFICATIONS. REMOVE LETTER CUTOUT FROM OVERLAY FILM TO ALLOW WHITE BACKGROUND TO SHOW THROUGH. LETTERING SHALL CONFIRM TO MUTCD/FHWA SERIES B "GOTHIC" FONT.

4. SIGN MOUNTING BRACKETS:

POST CAP - TAPCO MODEL #037-00002 OR EQUIVALENT
 CROSS BRACKET - TAPCO MODEL #037-00008 OR EQUIVALENT

5. CONTRACTORS SHALL SUBMIT A MATERIAL SUBMITTAL TO CAPITAL PROJECTS & ENGINEER AND PUBLIC WORKS DEPARTMENTS FOR APPROVAL PRIOR TO FABRICATION OF ANY STREET SIGNS TO BE INSTALLED WITHIN THE ROW.

SHT 2 OF 2

	DATE ISSUED: DECEMBER 18, 2018		TITLE	
	REVISION	DATE	BY	STREET NAME SIGN PLATE DETAIL
	1ST REVISION	1/28/19	MS	
			SCALE: N.T.S.	DRAWING No. RDWY-11.2